

ARCTIC™ 6% AFFF FOAM CONCENTRATE



TYPICAL PHYSICAL PROPERTIES AT 77 °F (25 °C)

Appearance: Clear, light yellow liquid
Freezing Point: 32°F (0°C)
 (No quality loss after thawing)
Maximum Storage Temp: 120°F (49°C)
pH: 7.0 - 8.5
Refractive Index: 1.3400 - 1.3450
Specific Gravity: 1.005 - 1.025
Viscosity: 1.7 - 3.7 cSt*
Sediments: < 0.05%
 *Cannon - Fenske Viscometer



APPLICATION

ARCTIC 6% AFFF foam concentrate can be applied to Class B hydrocarbon fuel fires. It is not intended for use on Class B polar solvent fuels. The foam can be used to prevent re-ignition of a liquid spill and control hazardous vapors. Foam discharge devices such as air aspirating, as well as, non-air aspirating equipment can be used to obtain maximum results. The product is mixed 6 parts foam concentrate to 94 parts water. It may also be used as a 6% pre-mix solution. ARCTIC 6% AFFF foam is compatible with most powder (dry chemical) agents.

PERFORMANCE

Fire Performance

ARCTIC 6% AFFF foam concentrate has been tested to and meets the fire performance test criteria of Underwriters Laboratories, Inc. (UL) Standard 162, Underwriters' Laboratories of Canada (ULC) Standard S564, European Standard EN 1568 Part 3 and International Civil Aviation Organization (ICAO) Level B.

Foam Proportioning

ARCTIC 6% AFFF foam concentrate can be proportioned at the proper foam solution percentage using most common proportioning devices such as:

- Eductors
- Inline balance pressure proportioners
- Ratio controllers
- Self-inducting nozzles

DESCRIPTION

ARCTIC™ 6% AFFF foam concentrate from SOLBERG is a synthetic foam concentrate used to effectively extinguish Class B hydrocarbon fuel fires at 6% solution. ARCTIC 6% AFFF foam provides rapid extinguishment and excellent burn back characteristics and can be used with fresh, salt and brackish water.

STORAGE

The storage temperature range for ARCTIC 6% AFFF foam concentrate is 35°F to 120°F (1.7°C to 49°C).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 20 years.

COMPATIBILITY

ARCTIC 6% AFFF foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing of foam concentrates, consult Perimeter Solutions Technical Services.

Materials of Construction Capability

ARCTIC 6% AFFF foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about material compatibility, consult Perimeter Solutions Technical Services.

INSPECTION

SOLBERG ARCTIC 6% AFFF foam concentrate or pre-mix solutions should be inspected annually per National Fire Protection Association (NFPA) Standards 11 and 25. A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

CERTIFICATIONS

SOLBERG manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam's physical parameters and finished product's fire performance. A Certificate of Analysis (CoA) is available for every batch.

ARCTIC™ 6% AFFF FOAM CONCENTRATE

ARCTIC 6% AFFF foam concentrate is Underwriters Laboratories, Inc. Listed in accordance with UL 162 (Standard for Safety for Foam Equipment and Liquid Concentrates), Underwriters' Laboratories of Canada Listed (Standard for Category 1 Foam Liquid Concentrates ULC S564), Witnessed and Certified by DNV-GL to European Norm (EN) Standard 1568

Part 3 and International Civil Aviation Organization (ICAO) Level B Certified.

ORDERING INFORMATION

ARCTIC 6% AFFF foam concentrate is available in pails, drums, totes and bulk quantities.

ORDERING INFORMATION

| Part No. | Description | Approximate Shipping Weight | Approximate Cube |
|----------|--|-----------------------------|--|
| 20246 | ARCTIC 6% AFFF, 5 gallon (20 litre) pail | 45 lb (21 kg) | 1.25 ft ³ (0.04 m ³) |
| 20247 | ARCTIC 6% AFFF, 55 gallon (200 litre) drum | 495 lb (224 kg) | 11.83 ft ³ (0.33 m ³) |
| 20248 | ARCTIC 6% AFFF, 265 gallon (1000 litre) tote | 2465 lb (1118 kg) | 50.05 ft ³ (1.42 m ³) |
| 20249 | ARCTIC 6% AFFF, bulk | Call Customer Services | |



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit: www.Perimeter-Solutions.com

UNITED STATES

10667 Jersey Blvd.
Rancho Cucamonga, CA 91730
Tel: +1 (920) 593-9445
salesfoamusa@perimeter-solutions.com

EMEA

Polígono Industrial de Baiña, Parcela 23
33682 Baiña-Mieres (Asturias) – Spain
Tel: +34 985 24 29 45
salesfoamemea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 2760 – Australia
Tel: +61 2 9673 5300
salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.