

PHOS-CHEK® 3x3% AR-AFFF

DESCRIPTION

Phos-Chek® 3x3% AR-AFFF foam concentrate is a mixture of water, hydrocarbon surfactants, solvents, C6 fluorosurfactants and fluoropolymers. The product is proportioned at 3% for both hydrocarbon and polar solvent fuel fires. PHOS-CHEK 3x3% AR-AFFF is UL listed and FM approved for both gentle and forceful applications when diluted with fresh, salt, and brackish water. PHOS-CHEK 3x3% AR-AFFF is versatile foam for use in both fixed foam systems and emergency response. It is the choice by many municipal and industrial fire departments. PHOS-CHEK 3x3% AR-AFFF can be used with standard proportioning equipment, foam discharge devices, bladder tank/ proportioner systems, foam chambers, foam makers, sprinklers, in-line foam proportioners, and self-inducting type nozzles.

APPLICATIONS

PHOS-CHEK 3x3% AR-AFFF is used in fire suppression systems and manual applications to fight a broad range of Class B flammable liquid fires including hydrocarbon fuels such as gasoline and diesel, and on polar solvent fuels such as ketones and alcohols. Typical applications include storage tanks, loading racks, docks, process areas, warehouses, and is an excellent vapor suppressor for flammable liquid spills.

APPROVAL CERTIFICATIONS

UL 162 Listed, EN 1568-3:2008 (Class IA) and EN 1568-4:2008 (Class IB) Approved. This concentrate is only FM Approved in conjunction with the specific proportioning and discharge devices as shown in the Approval Guide (www.ApprovalGuide.com).

ALCOHOL RESISTANT – AQUEOUS FILM FORMING FOAM CONCENTRATE



TYPICAL PHYSICAL PROPERTIES [AT 77 °F (25 °C)]

Appearance	Light yellow non-Newtonian liquid
Specific Gravity	1.000 – 1.040
pH	7.0 ± 0.5
Viscosity (LV-4 Spindle @ 30 RPM)*	2500 ± 400 cP
Refractive Index	1.3500 – 1.3600
Lowest Temperature for Use	35 °F (1.7 °C)
Freezing Point	25 °F (-4 °C)

VISCOSITY

@ 35 °F (1.7 °C)	LV-4 Spindle @ 30 RPM*	2920 ± 500 cP
@ 68 °F (20 °C)	LV-4 Spindle @ 30 RPM*	2800 ± 500 cP

*Brookfield LVT

STORAGE AND HANDLING

The concentrate should be stored at temperatures between 35 °F (1.7 °C) and 120 °F (49 °C)**, preferably in the original containers, approved bladder tanks, stainless steel, high density polyethylene, fiberglass or epoxy lined tanks. Concentrate piping acceptable materials of construction include stainless steel (either 304 or 316), some plastic piping including fiberglass and PVC, red brass, and black iron as long as the system is completely flooded eliminating the air/foam concentrate/carbon steel interface. Avoid permanent contact with carbon steel, iron, some copper alloys, & aluminum when the piping material and concentrate will be exposed to air. Galvanized piping should not be used in direct contact with the foam concentrate.

**EN APPROVAL: 35 °F (1.7 °C) and 122 °F (50 °C)

SHELF LIFE, INSPECTION AND TESTING

The shelf life of any foam concentrate is maximized by proper storage conditions and maintenance. Factors affecting shelf life are wide temperature fluctuation, evaporation, dilution, and contamination by foreign materials. Properly stored PHOS-CHEK Class B AR-AFFF foam concentrates should have no significant loss of firefighting performance for 20+ years. However, the National Fire Protection Association (NFPA) recommends annual testing of all firefighting foams.



Foam concentrates are subject to evaporation, which accelerates when the product is exposed to air. Storage tanks should be sealed and fitted with a pressure vacuum vent to prevent free exchange of air.

HANDLING PRECAUTIONS

- For DETAILED SAFETY INFORMATION, please refer to the SDS.
- **Precautionary Measures:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary contact and removal of the material from the eyes, skin and clothing.
- **Eye Protection:** As a good industrial practice, the use of chemical goggles is recommended.
- **If in the eyes:** Flush with plenty of water.
- **Skin Protection:** Wear protective gloves when handling concentrate to minimize skin contact. Wash hands and contaminated skin after handling.
- **Respiratory Protection:** None required.
- For complete SDS, visit perimeter-solutions.com

PACKAGING**ORDERING INFORMATION**

PHOS-CHEK 3X3% AR-AFFF	lb.*	kg.*	Part #
5 Gallon Pail (20 litres)	43	19	10003970
55 Gallon Drum (200 litres)	468	212	10003969
265 Gallon Tote (1,000 litres)	2255	1023	10003968

*Approximate shipping weight

*Contact your local authorized PHOS-CHEK distributor or factory sales representative for additional details. perimeter-solutions.com



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:
www.Perimeter-Solutions.com

UNITED STATES

10667 Jersey Blvd.
Rancho Cucamonga, CA 91730
Tel: +1 800 682 3626
Tel: +1 909 983 0772
salesfoamusa@perimeter-solutions.com

EMEA

Polígono de Baiña, Parcela 23
33682 Mieres (Asturias)
Spain
Tel: +34 985 24 29 45
salesfoamemea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 2760 – Australia
Tel: +61 2 9673 5300
salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.